Please read and comply with these original instructions prior to the initial operation of your appliance and store them for later use or subsequent owners.

- Before first start-up it is definitely necessary to read the safety indications Nr. 5.956-249!
- The non-compliance of the operating and safety instructions may lead to damages of the appliance and to dangers for the operator and other persons.
- In case of transport damage inform vendor immediately

Contents

Environmental protection	EN1
Symbols in the operating in-	
structions	EN1
Proper use	EN2
Device elements	EN2
Start up	EN2
Operation	EN2
Transport	EN3
Storage	EN3
Maintenance and care	EN3
Troubleshooting	EN3
Warranty	EN4
Accessories and Spare Parts	EN4
CE declaration	EN4
Technical specifications	EN5

Environmental protection



The packaging material can be recycled. Please do not throw the packaging material into household waste; please send it for recycling.



Old appliances contain valuable materials that can be recycled; these should be sent for recycling. Batteries, oil, and similar substances must not enter the environment. Please dispose of your old appliances using appropriate collection systems.

Notes about the ingredients (REACH)

You will find current information about the ingredients at:

www.kaercher.com/REACH

Symbols in the operating instructions

△ Danger

Immediate danger that can cause severe injury or even death.

△ Warning

Possible hazardous situation that could lead to severe injury or even death.

Caution

Possible hazardous situation that could lead to mild injury to persons or damage to property.

EN - 1 9

Proper use

⚠ Warning

The appliance is not suitable for vacuuming dust which endangers health.

Caution

This unit is only to be used indoors.

- This vacuum cleaner is meant for dry cleaning of floors and walls.
- This appliance is suited for the commercial use, e.g. to clean buildings (offices, hotels, etc.), for handymen on construction sites, for carpenters and for interior remodeling.

Device elements

- 1 Fleece filter bag
- 2 Suction support
- 3 Suction hose
- 4 Nameplate
- 5 Carrying handle
- 6 Cable clamp
- 7 Power cord
- 8 Suction head
- 9 Suction head lock
- 10 Storage for accessories
- 11 Impeller
- 12 Steering roller
- 13 Dirt receptacle
- 14 Main switch
- 15 Pickup for floor nozzle (T 10/1 only)
- 16 Switch between hard surface/carpet (depending on model)
- 17 Floor nozzle
- 18 Suction pipe
- 19 Suction force regulator (continuous)
- 20 Bender
- 21 Main filter basket
- 22 Motor filter
- 23 Grid of the motor proction filter

Start up

The appliance can be operated in 2 ways:

- Operation with fleece filter bag or paper filter bag (option)
- 2 Operation without filter bag
- → Check whether main filter basket has been inserted into the appliance.

Installation of the filter bag

- → Release and remove the suction head.
- → Remove the main filter basket.
- → Install the fleece filter bag or the paper filter bag (option).
- → Insert main filter basket.
- → Insert and lock the suction head.

Operation

Turning on the Appliance

- → Plug in the main plug.
- → Switch on the appliance at the main switch.

Cleaning operations

- → Set the selection switch of the floor nozzle to hard surface or carpet.
- → Regulate the suction force on the suction force regulator (continuous).
- → Perform the cleaning operation.

Turn off the appliance

- → Switch off the appliance at the main switch.
- → Pull out the mains plug.

After each operation

- → Empty the container.
- → Vacuum and wipe the appliance inside and outside with a damp cloth.

Transport

Caution

Risk of injury and damage! Observe the weight of the appliance when you transport it

→ When transporting in vehicles, secure the appliance according to the guidelines from slipping and tipping over.

Storage

Caution

Risk of injury and damage! Note the weight of the appliance in case of storage. This appliance must only be stored in interior rooms.

Maintenance and care

⚠ Danger

First pull out the plug from the mains before carrying out any tasks on the machine.

Clean main filter basket

→ Main filter basket (washable), clean it under running water if necessary.

Caution

Risk of damage! Never insert the main filter basket while wet.

Replace motor protection filter

- → Release and remove the suction head.
- → Push the grids of the motor protection filter down, turn and remove.
- → Remove the motor protection filter.
- → Insert the new motor protection filter.
- → Insert the grid of the motor protection filter and lock it into place.
- → Insert and lock the suction head.

Troubleshooting

△ Danger

First pull out the plug from the mains before carrying out any tasks on the machine.

The appliance shuts off during the operation

- Motor thermal protector has responded.
- → Replace the fleece filter bag or paper filter bag (option).
- → Replace motor protection filter.
- → Check all parts for plugging.

Switching back on after the motor turbine has cooled off, after approx. 30 to 40 minutes.

Suction turbine does not run

- → Check cables, plugs and socket.
- → Turn on the appliance.

Suction capacity decreases

- → Remove choking of suction nozzle, suction tube or suction hose.
- → Replace the fleece filter bag or paper filter bag (option).
- Clean the main filter under running water.
- → Insert/lock the suction basket correctly.
- → Replace defective suction hose.
- → Replace motor protection filter.

Dust comes out while vacuuming

- → Replace the fleece filter bag or paper filter bag (option).
- → Check the fleece filter bag or paper filter bag (option).
- → Insert/lock the suction basket correctly.
- → Insert undamaged main filter basket.
- → Reinsert motor protection filter correctly.

Warranty

The warranty terms published by the relevant sales company are applicable in each country. We will repair potential failures of your appliance within the warranty period free of charge, provided that such failure is caused by faulty material or defects in manufacturing. In the event of a warranty claim please contact your dealer or the nearest authorized Customer Service centre. Please submit the proof of purchase.

Accessories and Spare Parts

- Only use accessories and spare parts which have been approved by the manufacturer. The exclusive use of original accessories and original spare parts ensures that the appliance can be operated safely and trouble free.
- At the end of the operating instructions you will find a selected list of spare parts that are often required.
- For additional information about spare parts, please go to the Service section at www.kaercher.com.

CE declaration

We hereby declare that the machine described below complies with the relevant basic safety and health requirements of the EU Directives, both in its basic design and construction as well as in the version put into circulation by us. This declaration shall cease to be valid if the machine is modified without our prior approval.

Product: Dry vacuum cleaner

Type: 1.527-xxx Relevant EU Directives 2006/42/EC (+2009/127/EC) 2004/108/EC

Applied harmonized standards

EN 55014-1: 2006 + A1: 2009 EN 55014-2: 1997 + A2: 2008

EN 60335-1 EN 60335-2-69

EN 61000-3-2: 2006 + A2: 2009

EN 61000-3-3: 2008

EN 62233: 2008

Applied national standards

-

5.957-804

The undersigned act on behalf and under the power of attorney of the company management.

H. Jenner

CEO

Head of Approbation

Authorised Documentation Representative S. Reiser

Alfred Kärcher GmbH Co. KG Alfred-Kärcher-Str. 28 - 40 71364 Winnenden (Germany)

Phone: +49 7195 14-0 Fax: +49 7195 14-2212

Winnenden, 2010/12/01

Technical specifications

		T 7/1	T 10/1	
Mains voltage	V	220-240	220-240	
Frequency	Hz	1~ 50/60	1~ 50/60	
Max. performance	W	1200	1250	
Container capacity	I	7	10	
Air volume (max.)	I/s	55	61	
Negative pressure (max.)	kPa (mbar)	24,5 (245)	24,4 (244)	
Protective class		II	II	
Suction hose connection (C-DN/C-ID)	mm	32	32	
Length x width x height	mm	350 x 310 x 340	355 x 310 x 385	
Weight	kg	5,3	6,0	
Max. ambient temperature	°C	+40	+40	
Values determined to EN 60335-2-69				
Sound pressure level L _{pA}	dB(A)	66	66	
Uncertainty K _{pA}	dB(A)	1	1	
Hand-arm vibration value	m/s ²	<2,5	<2,5	
Uncertainty K	m/s ²	0,2	0,2	

Power cord	H05V2V2-F 2x1,0 mm ²		
T 7/1	Part no.:	Cable length	
EUR	6.649-241.0	7,5 m	
GB	6.649-264.0	7,5 m	
СН	6.649-273.0	10 m	

Power cord	H05V2V2-F 2x1,0 mm ²		
T 10/1	Part no.:	Cable length	
EUR	6.649-296.0	10 m	
GB	6.649-297.0	10 m	
СН	6.649-273.0	10 m	
AUS	6.649-328.0	10 m	

EN - 5 13